

مشخصات کلی دستگاه گریندینگ مغناطیسی

Grinding surface of table (mm)	300x600 (12"x24")
Max. grinding surface (mm)	300x600 (12"x24")
Max. distance center of spindle to table (mm)	500 [(Option:600mm(24")]
Table speed approx (M/min)	5~25
Table guideway	V& Flat way
Auto cross feed increment approx.(mm)	0.5 -20
Rapid power cross feed (mm/min)	1100(60HZ) / 900 (50Hz)
Cross feed on hand wheel (mm)	5/rev;0.02/gra.
Rapid power hand elevation (mm/min)	550(Hz) / 450(50Hz)
Vertical feed on hand wheel (mm)	2/rev;0.01/gra.
Vertical feed on Micro feed attachment (mm)	0.001/gra
Wheel speed (R.P.M)	1750 (60Hz) / 1450 (50Hz)
Wheel dimension (mm)	355x38x127
Spindle motor (HP)	5
Hydraulic pump motor (HP)	1
Auto cross feed motor	1/5HP
Rapid head elevation motor	1/5HP
Coolant Pump	1/8HP
Machine net weight (kgs)	1700
Packing gross weight (kgs)	1950
Machine dimensions (LxWxH) mm	2630x1550x1800
Packing dimension(LXWXH) cm	230x179x220